

## Metric Conversions

|       |   |           |       |                     |           |
|-------|---|-----------|-------|---------------------|-----------|
| 1 kg  | = | 2.2046 lb | 50 kg | =                   | 110.23 lb |
| 5 kg  | = | 11.023 lb | 60 kg | =                   | 132.28 lb |
| 10 kg | = | 22.046 lb | 70 kg | =                   | 154.32 lb |
| 20 kg | = | 44.092 lb | 75 kg | =                   | 165.35 lb |
| 30 kg | = | 66.139 lb |       |                     |           |
| 35 kg | = | 77.162 lb |       |                     |           |
| 40 kg | = | 88.185 lb |       |                     |           |
|       |   | 1 lb      | =     | 0.4536 kg           |           |
|       |   | 1 cwt     | =     | 50.8023 kg          |           |
|       |   | 1 ton     | =     | 1016.05 kg          |           |
|       |   | 1 Tonne   | =     | 1000 kg             |           |
|       |   | 1 Acre    | =     | 0.4047 Hectare (ha) |           |
|       |   | 1 Hectare | =     | 2.4710 Acres (ac)   |           |

## Conversion Tables – Rainfall

|               |   |                 |               |   |                  |
|---------------|---|-----------------|---------------|---|------------------|
| <b>1 inch</b> | = | <b>25.40 mm</b> | <b>100 mm</b> | = | <b>3.937 in.</b> |
| 5 pts         | = | 1.27 mm         | 5 mm          | = | 0.20 in.         |
| 10 pts        | = | 2.54 mm         | 10 mm         | = | 0.39 in.         |
| 0.25 in.      | = | 6.35 mm         | 25 mm         | = | 0.98 in.         |
| 0.50 in.      | = | 12.70 mm        | 50 mm         | = | 1.97 in.         |
| 1 in.         | = | 25.40 mm        | 100 mm        | = | 3.94 in.         |
| 5 in.         | = | 127.00 mm       | 150 mm        | = | 5.91 in.         |
| 10 in.        | = | 254.00 mm       | 200 mm        | = | 7.87 in.         |
| 20 in.        | = | 508.00 mm       | 250 mm        | = | 9.84 in.         |
| 30 in.        | = | 762.00 mm       | 300 mm        | = | 11.81 in.        |
| 40 in.        | = | 1016.00 mm      | 400 mm        | = | 15.75 in.        |

## Cyclone® Fencing Wire Table Of Gauges And Lengths

| Diameter             | Nearest Gauge | Length of 25 kg Coil |                 |
|----------------------|---------------|----------------------|-----------------|
|                      |               | Metres               | Yards (approx.) |
| 2.00 mm              | 14            | 1013                 | 1108            |
| 2.50 mm              | 12.5          | 648                  | 711             |
| 3.15 mm              | 10            | 408                  | 446             |
| 3.55 mm              | 9             | 321                  | 351             |
| 4.00 mm              | 8             | 253                  | 277             |
| 4.50 mm              | 7             | 200                  | 219             |
| <b>Barbed (lowa)</b> |               |                      |                 |
| 2.50 mm x 75 mm      | 12.5ga x 3"   | 225                  | 246             |
| 2.50 mm x 150 mm     | 12.5ga x 6"   | 255                  | 279             |